# **To Filter or not to Filter:** Measuring the Benefits of **Registering in the RPKI Today**

Passive and Active Measurement Conference 2020

**Cecilia Testart** MIT

Alberto Dainotti

CAIDA, UC San Diego




Philipp Richter MIT


**Alistair King** CAIDA, UC San Diego

**David Clark** MIT


















































BGP lacks a mechanism for route validation.



# The Resource Public Key Infrastructure


- The RPKI is a framework to secure BGP using cryptographic records to validate prefix and origin in BGP announcements.
- Route Origin Authorizations (ROAs) map IP prefixes with valid AS origins.
- Networks can use the RPKI to validate announcements in BGP.






# The Resource Public Key Infrastructure

- The RPKI is a framework to secure BGP using cryptographic records to validate prefix and origin in BGP announcements.
- Route Origin Authorizations (ROAs) map IP prefixes with valid AS origins.
- Networks can use the RPKI to validate announcements in BGP.




About 20% of IP prefixes in BGP are covered by valid ROAs.






















































### Only anecdotal evidence of RPKI enforcement.



## **Research** goal

### To what degree does registration in the RPKI protect a network from illicit announcements of their prefixes?

- Measure RPKI enforcement over time (i)
- (ii) Study the visibility of prefix origin pairs depending on their RPKI status
- (iii) Analyze visibility of prefixes in the case of conflicts



# **RPKI and BGP dataset**

### • **RPKI** data:

- Daily list of validated ROAs from RIPE NCC RPKI validator (Sep. 2019).
- Historical lists of validated ROAS made available by Chung et al (Apr. 2017 - Sep. 2019).

RPKI Validator Trust Anchors ROAs Ignore Filters Whitelist BGP Preview Announcement Preview

### **Validated ROAs**

ASN	Prefix	Max Length	Trust Anchors	URI of RC
3335	1.0.0.0/24	24	APNIC RPKI Root	ê
335	1.1.1.0/24	24	APNIC RPKI Root	ê
88	1.9.0.0/16	24	APNIC RPKI Root	ð
5037	1.9.12.0/24	24	APNIC RPKI Root	ð
1514	1.9.21.0/24	24	APNIC RPKI Root	ê
120	1.9.23.0/24	24	APNIC RPKI Root	ê
5077	1.9.31.0/24	24	APNIC RPKI Root	ð
1514	1.9.65.0/24	24	APNIC RPKI Root	ê
462	1.34.0.0/15	24	APNIC RPKI Root	ê
760	1.36.0.0/16	16	APNIC RPKI Root	ð

#### Export

Here you are able to export the complete ROA data set for use in an existing BGP decision making workflow. The output will be in CSV or JSON format and consist of all validated ROAs, minus your ignore filter entries, plus your whitelist entries.

Get ISON

RIPE NCC Copyright ©2009-2019 the Réseaux IP Européens Network Coordination Centre RIPE NCC. All rights restricted. Version: 3.0-SNAPSHOT.





# **RPKI and BGP dataset**

### • **RPKI** data:

- Daily list of validated ROAs from RIPE NCC RPKI validator (Sep. 2019).
- Historical lists of validated ROAS made available by Chung et al (Apr. 2017 - Sep. 2019).
- Longitudinal BGP dataset:
  - RIB dumps from all RIPE RIS and RouteViews collectors on the first day of the month (Apr. 2017 - Jan. 2020).

RPKI Validator

Trust Anchors ROAs Ignore Filters Whitelist BGP Preview Announcement Preview

### **Validated ROAs**

ASN	Prefix	Max Length	Trust Anchors	URI of RC
3335	1.0.0.0/24	24	APNIC RPKI Root	ê
335	1.1.1.0/24	24	APNIC RPKI Root	ê
88	1.9.0.0/16	24	APNIC RPKI Root	ð
5037	1.9.12.0/24	24	APNIC RPKI Root	ð
1514	1.9.21.0/24	24	APNIC RPKI Root	ê
120	1.9.23.0/24	24	APNIC RPKI Root	ê
5077	1.9.31.0/24	24	APNIC RPKI Root	ð
1514	1.9.65.0/24	24	APNIC RPKI Root	ê
462	1.34.0.0/15	24	APNIC RPKI Root	ê
760	1.36.0.0/16	16	APNIC RPKI Root	ð

#### Export

Here you are able to export the complete ROA data set for use in an existing BGP decision making workflow. The output will be in CSV or JSON format and consist of all validated ROAs, minus your ignore filter entries, plus your whitelist entries.

🔗 RIPE NCC Copyright ©2009-2019 the Réseaux IP Européens Network Coordination Centre RIPE NCC. All rights restricted. Version: 3.0-SNAPSHOT.





# **RPKI and BGP dataset**

### • **RPKI** data:

- Daily list of validated ROAs from RIPE NCC RPKI validator (Sep. 2019).
- Historical lists of validated ROAS made available by Chung et al (Apr. 2017 - Sep. 2019).
- Longitudinal BGP dataset:
  - RIB dumps from all RIPE RIS and RouteViews collectors on the first day of the month (Apr. 2017 - Jan. 2020).

### • Fine-Grained BGP dataset:

 All BGP updates from RIPE RIS and RouteViews collector peers to compute (prefix, origin AS, visibility, timestamp) every 5 min (Sep.2019).

RPKI Validator

### Validated ROAs

ASN	Prefix	Max Length	Trust Anchors	URI of R
13335	1.0.0.0/24	24	APNIC RPKI Root	e
13335	1.1.10/24	24	APNIC RPKI Root	e
4788	1.9.0.0/16	24	APNIC RPKI Root	e
65037	1.9.12.0/24	24	APNIC RPKI Root	e
24514	1.9.21.0/24	24	APNIC RPKI Root	e
65120	1.9.23.0/24	24	APNIC RPKI Root	Q
65077	1.9.31.0/24	24	APNIC RPKI Root	e
24514	1.9.65.0/24	24	APNIC RPKI Root	e
3462	1.34.0.0/15	24	APNIC RPKI Root	e
4760	1.36.0.0/16	16	APNIC RPKI Root	Ð


#### Export

for use in an existing BGP decision making workflow. The output will be in CSV or JSON format and consist of all validated ROAs, minus your ianore filter entries, plus your whitelist entries


RIPE NCC Copyright ©2009-2019 the Réseaux IP Européens Network Coordination Centre RIPE NCC. All rights restricted. Version: 3.0-SNAPSHOT

















More invalid information



Two steps to detect filtering:




More invalid information



Two steps to detect filtering:

(1) Select full-feeder ASes: ASes that share their full routing table with BGP collectors




More invalid information




Two steps to detect filtering:

(1) Select full-feeder ASes: ASes that share their full routing table with BGP collectors



Two steps to detect filtering:


(1) Select full-feeder ASes: ASes that share their full routing table with BGP collectors



Two steps to detect filtering:

(1) Select full-feeder ASes: ASes that share their full routing table with BGP collectors


(2) Select ASes forwarding low counts of RPKI-invalid announcements.



Two steps to detect filtering:

(1) Select full-feeder ASes: ASes that share their full routing table with BGP collectors

(2) Select ASes forwarding low counts of **RPKI-invalid** announcements.




### **Detecting RPKI filtering**

Two steps to detect filtering:

(1) Select full-feeder ASes: ASes that share their full routing table with BGP collectors

(2) Select ASes forwarding low counts of **RPKI-invalid** announcements.





## Detecting RPKI filtering

Two steps to detect filtering:


(1) Select full-feeder ASes: ASes that share their full routing table with BGP collectors

(2) Select ASes forwarding low counts of **RPKI-invalid** announcements.
















Major increase between April and August 2019.






























We detect when ASes start enforcing RPKI filtering.






We detect when ASes start enforcing RPKI filtering.


Month






We detect when ASes start enforcing RPKI filtering.





We detect when ASes start enforcing RPKI filtering.





We detect when ASes start enforcing RPKI filtering. No ASes filters all RPKI-invalid announcements.



# Reasons for partial filtering

- Selective RPKI Trust Anchor (TA) filtering: some networks do not consider ROAs from the ARIN TA, resulting in more invalid prefix-origins propagated by them.
- Selective filtering depending on AS relationships: several network operators announced to implement filtering only for routes received from peers, but not customer networks.
- Operational deployment issues: some network operators reported compatibility issues with RPKI validator implementations and router software, prompting them to deploy RPKI-filtering in a subset of their border routers.









#### **Prefix-origin timelines**

IPv4 total

**RPKI** covered

**RPKI-valid** 

**RPKI-invalid** 

IPv6 total

**RPKI** covered

**RPKI-valid** 

**RPKI-invalid** 

Count	%
883,400	100%
147,870	17%
139,537	16%
8,333	1%
91,313	100%
17,656	21%
362	19%
1155	2%

#### **Prefix-origin timelines**

IPv4 total

**RPKI** covered

**RPKI-valid** 

**RPKI-invalid** 

IPv6 total

**RPKI** covered

**RPKI-valid** 

**RPKI-invalid** 

	%	Count
	100%	883,400
Covered IPv4	(17%)	147,870
	16%	139,537
	1%	8,333
	100%	91,313
Covered IPv6	(21%)	17,656
	19%	362
	2%	1155

#### **Prefix-origin timelines**

IPv4 total

**RPKI** covered

**RPKI-valid** 

**RPKI-invalid** 

IPv6 total

**RPKI** covered

**RPKI-valid** 

**RPKI-invalid** 

	%	Count
	100%	883,400
	17%	147,870
	16%	139,537
Invalids IPv4	1%	8,333
	100%	91,313
	21%	17,656
	19%	362
Invalids IPv6	2%	1155

#### **Prefix-origin timelines**

IPv4 total

**RPKI** covered

**RPKI-valid** 

**RPKI-invalid** 

IPv6 total


**RPKI** covered

**RPKI-valid** 


**RPKI-invalid** 

IPv4 and IPv6 results follow similar trends


	%	Count
	100%	883,400
	17%	147,870
	16%	139,537
Invalids IPv4	1%	8,333
	100%	91,313
	21%	17,656
	19%	362
Invalids IPv6	2%	1155













RPKI-invalid prefixes are less visible than RPKI-valid or -unknown:






#### **RPKI-invalid** prefixes are less visible than RPKI-valid or -unknown: - large share (20%) of very localized RPKI-invalid prefixes






RPKI-invalid prefixes are less visible than RPKI-valid or -unknown:
- large share (20%) of very localized RPKI-invalid prefixes
- RPKI-invalid prefixes never reach the higher levels of visibility






















































### Prefix-origin visibility in the case of MOAS conflicts







#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts.




#### RPKI-valid prefixes dominate visibility in MOAS conflicts. RPKI helps protect legitimate prefix from illicit announcements.




# RPKI-valid prefixes dominate visibility in MOAS conflicts. RPKI helps protect legitimate prefix from illicit announcements.




# RPKI-valid prefixes dominate visibility in MOAS conflicts. RPKI helps protect legitimate prefix from illicit announcements.




# RPKI-valid prefixes dominate visibility in MOAS conflicts. RPKI helps protect legitimate prefix from illicit announcements.







































































































































RPKI-invalid sub prefixes announcements have 10-15% less visibility.





RPKI-invalid sub prefixes announcements have 10-15% less visibility.
RPKI reduces reachability of subMOAS and subprefix path hijacks.





# Key takeaways


- to filter RPKI-invalid announcements.
- Passive method allows for continuous monitoring of RPKI enforcement.
- First study to measure the **benefit** of registering prefixes in the **RPKI**.
- RPKI enforcement starts to bring real value to networks:
  - limits the propagation of illicit announcements,
  - reduces visibility of challenging announcements in case of conflicts.

#### Longitudinal analysis of RPKI enforcement shows growing number of ISPs begin



# Key takeaways

- to filter RPKI-invalid announcements.
- Passive method allows for **continuous monitoring** of RPKI enforcement.
- First study to measure the benefit of registering prefixes in the RPKI.
- RPKI enforcement starts to bring real value to networks:
  - limits the propagation of illicit announcements,
  - reduces visibility of challenging announcements in case of conflicts.



#### Longitudinal analysis of **RPKI enforcement** shows **growing** number of ISPs begin

