

# HIGH PERFORMANCE COMPUTING

## ASSIGNMENT 3

The goal of this assignment is to learn to use MPI and to measure MPI communication latency and bandwidth.

- (a) **10 marks.** The ping-pong benchmark is a way to measure the communication time between two processes. Conceptually, process 0 sends a message to process 1. After process 1 receives the message, it immediately sends a message to process 0. This is called a “ping-pong.” The time for sending a message is half the time for a ping-pong. Write a code that performs this ping-pong benchmark. It should have the following features: 1) the message length can be set by the user, 2) two ping-pongs are performed simultaneously (started by each of process 0 and process 1), which is more like realistic applications. It may be difficult to measure the time for a single ping-pong, so be sure to measure the time for multiple ping-pongs together.
- (b) **10 marks.** Run the ping-pong benchmark and measure the time for two processes on the same node. Then run the benchmark on two processes on different nodes. Note that it may be tricky to make sure that two processes are on different nodes. Plot the time for a single message as a function of message length, from 1 byte to  $2^{20} = 1048576$  bytes. Also plot the communication rate (GByte/s), also as a function of message length. What is the communication latency and bandwidth for the two cases?
- (c) **5 marks.** Submit a short report of your results as a pdf file. Marks will be given for the clarity of your report, labeling your graph axes, etc. Briefly explain why you think your results are reasonable. Include a listing of your code in the pdf file.