

Ninio, J. and Stevens, K. A. (2000) Variations on the Hermann grid: an extinction illusion. *Perception*, 29, 1209-1217.

## Variations on the Hermann grid: an extinction illusion

---

### Jacques Ninio

Laboratoire de Physique Statistique<sup>(1)</sup>, École Normale Supérieure, 24 rue Lhomond,  
75231 Paris cedex 05, France; e-mail: [jacques.ninio@lps.ens.fr](mailto:jacques.ninio@lps.ens.fr)

### Kent A Stevens

Department of Computer Science, Deschutes Hall, University of Oregon, Eugene, OR 97403, USA;  
e-mail: [kent@cs.uoregon.edu](mailto:kent@cs.uoregon.edu)

Received 21 September 1999, in revised form 21 June 2000

---


**Abstract.** When the white disks in a scintillating grid are reduced in size, and outlined in black, they tend to disappear. One sees only a few of them at a time, in clusters which move erratically on the page. Where they are not seen, the grey alleys seem to be continuous, generating grey crossings that are not actually present. Some black sparkling can be seen at those crossings where no disk is seen. The illusion also works in reverse contrast.

The Hermann grid (Brewster 1844; Hermann 1870) is a robust illusion. It is classically presented as a two-dimensional array of black squares, separated by rectilinear alleys. It is thought to be caused by processes of local brightness computation in arrays of

# Fundamental matrix

---

Let  $p$  be a point in left image,  $p'$  in right image



Epipolar relation

- $p$  maps to epipolar line  $l'$
- $p'$  maps to epipolar line  $l$

Epipolar mapping described by a 3x3 matrix  $F$

$$p'^T F p = 0$$

# Fundamental matrix

---

This matrix  $F$  is called

- the “Essential Matrix”
  - when image intrinsic parameters are known
- the “Fundamental Matrix”
  - more generally (uncalibrated case)

Can solve for  $F$  from point correspondences

- Each  $(p, p')$  pair gives one linear equation in entries of  $F$

$$p'^T F p = 0$$

- $F$  has 9 entries, but really only 7 or 8 degrees of freedom.

# Today's lecture


- Depth Estimation from Stereo Matching (Sparse correspondence to Dense Correspondence)

# *Stereo Matching*

---




# Stereo image rectification



# Stereo image rectification

- Reproject image planes onto a common plane parallel to the line between camera centers
- Pixel motion is horizontal after this transformation
- Two homographies (3x3 transform), one for each input image reprojection
- C. Loop and Z. Zhang. [Computing Rectifying Homographies for Stereo Vision](#). IEEE Conf. Computer Vision and Pattern Recognition, 1999.





# Rectification example



# The correspondence problem

- Epipolar geometry constrains our search, but we still have a difficult correspondence problem.

# Fundamental Matrix + Sparse correspondence

## Photo Tourism Exploring photo collections in 3D

Noah Snavely   Steven M. Seitz   Richard Szeliski  
*University of Washington*   *Microsoft Research*

SIGGRAPH 2006

# Fundamental Matrix + Dense correspondence

## The Visual Turing Test for Scene Reconstruction Supplementary Video

Qi Shan<sup>+</sup>   Riley Adams<sup>+</sup>   Brian Curless<sup>+</sup>  
Yasutaka Furukawa<sup>\*</sup>   Steve Seitz<sup>++</sup>

<sup>+</sup>University of Washington   <sup>\*</sup>Google

3DV 2013

# SIFT + Fundamental Matrix + RANSAC


Despite their scale invariance and robustness to appearance changes, SIFT features are *local* and do not contain any global information about the image or about the location of other features in the image. Thus feature matching based on SIFT features is still prone to errors. However, since we assume that we are dealing with rigid scenes, there are strong geometric constraints on the locations of the matching features and these constraints can be used to clean up the matches. In particular, when a rigid scene is imaged by two pinhole cameras, there exists a  $3 \times 3$  matrix  $F$ , the *Fundamental matrix*, such that corresponding points  $x_{ij}$  and  $x_{ik}$  (represented in homogeneous coordinates) in two images  $j$  and  $k$  satisfy<sup>10</sup>:

$$x_{ij}^\top F x_{ij} = 0. \quad (3)$$

A common way to impose this constraint is to use a greedy randomized algorithm to generate suitably chosen random estimates of  $F$  and choose the one that has the largest support among the matches, i.e., the one for which the most matches satisfy (3). This algorithm is called Random Sample Consensus (RANSAC)<sup>6</sup> and is used in many computer vision problems.

## Building Rome in a Day

# Sparse to Dense Correspondence




## Building Rome in a Day

By Sameer Agarwal, Yasutaka Furukawa, Noah Snavely, Ian Simon, Brian Curless, Steven M. Seitz, Richard Szeliski  
Communications of the ACM, Vol. 54 No. 10, Pages 105-112



# Structure from motion (or SLAM)

- Given a set of corresponding points in two or more images, compute the camera parameters and the 3D point coordinates



# Structure from motion ambiguity

- If we scale the entire scene by some factor  $k$  and, at the same time, scale the camera matrices by the factor of  $1/k$ , the projections of the scene points in the image remain exactly the same:

$$\mathbf{x} = \mathbf{P}\mathbf{X} = \left( \frac{1}{k} \mathbf{P} \right) (k \mathbf{X})$$

It is impossible to recover the absolute scale of the scene!



How do we know the scale of image content?











# Bundle adjustment

- Non-linear method for refining structure and motion
- Minimizing reprojection error

$$E(\mathbf{P}, \mathbf{X}) = \sum_{i=1}^m \sum_{j=1}^n D(\mathbf{x}_{ij}, \mathbf{P}_i \mathbf{X}_j)^2$$



# Correspondence problem




Multiple match hypotheses satisfy epipolar constraint, but which is correct?

Figure from Gee & Cipolla 1999

# Correspondence problem

- Beyond the hard constraint of epipolar geometry, there are “soft” constraints to help identify corresponding points
  - Similarity
  - Uniqueness
  - Ordering
  - Disparity gradient
- To find matches in the image pair, we will assume
  - Most scene points visible from both views
  - Image regions for the matches are similar in appearance

# Dense correspondence search




For each epipolar line

For each pixel / window in the left image

- compare with every pixel / window on same epipolar line in right image
- pick position with minimum match cost (e.g., SSD, normalized correlation)


# Correspondence search with similarity constraint




- Slide a window along the right scanline and compare contents of that window with the reference window in the left image
- Matching cost: SSD or normalized correlation




# Correspondence search with similarity constraint





# Correspondence search with similarity constraint



# Correspondence problem




Intensity profiles



- Clear correspondence between intensities, but also noise and ambiguity

# Correspondence problem



Neighborhoods of corresponding points are similar in intensity patterns.

# Correlation-based window matching



left image band (x)


# Correlation-based window matching



left image band ( $x$ )


right image band ( $x'$ )

# Correlation-based window matching



left image band ( $x$ )

right image band ( $x'$ )




↑  
cross  
correlation

→  
disparity =  $x' - x$





# Correlation-based window matching






# Correlation-based window matching




Textureless regions are non-distinct; high ambiguity for matches.


# Effect of window size



# Effect of window size





$W = 3$




$W = 20$

Want window large enough to have sufficient intensity variation, yet small enough to contain only pixels with about the same disparity.



# Results with window search



Window-based matching  
(best window size)





Ground truth

# Better solutions

- Beyond individual correspondences to estimate disparities:
- Optimize correspondence assignments jointly
  - Scanline at a time (e.g. dynamic programming)
  - Full 2D grid (e.g. graph cuts)
  - Approximate 2D solution (e.g. semi-global matching)

# Scanline stereo

- Try to coherently match pixels on the entire scanline
- Different scanlines are still optimized independently










# Matching using Epipolar Lines


Left Image



Right Image



For a patch in left image  
Compare with patches along  
same row in right image




Match Score Values

# Matching using Epipolar Lines

Left Image




Right Image



Select patch with highest  
match score.

Repeat for all pixels in  
left image.




Match Score Values

# Example: 5x5 windows NCC match score



Computed disparities





Ground truth

Black pixels: bad disparity values,  
or no matching patch in right image



# Occlusions: No matches




# Effects of Patch Size



5x5 patches

Smoother in some areas



11x11 patches

Loss of finer details

# Adding Intra-Scanline Consistency

So far, each left image patch has been matched independently along the right epipolar line.

This can lead to errors.


We would like to enforce some consistency among matches in the same row (scanline).



# Disparity Space Image

First we introduce the concept of DSI.

The DSI for one row represents pairwise match scores between patches along that row in the left and right image.




# Disparity Space Image (DSI)

Left Image



Right Image




Dissimilarity Values  
(1-NCC) or SSD

# Disparity Space Image (DSI)

Left Image



Right Image



Dissimilarity Values  
(1-NCC) or SSD




Robert Collins  
CSE486, Penn State

# Disparity Space Image (DSI)

Left Image




Right Image





Dissimilarity Values  
(1-NCC) or SSD

# Disparity Space Image (DSI)

Left Image



DSI




Dissimilarity Values

Enter each vector of  
match scores as a  
column in the DSI

# Disparity Space Image


Left scanline






# Disparity Space Image

Left scanline



# DSI and Scanline Consistency


Assigning disparities to all pixels in left scanline now amounts to finding a connected path through the DSI






# Lowest Cost Path

We would like to choose the “best” path.

Want one with lowest “cost” (Lowest sum of dissimilarity scores along the path)



# Cox et.al. Stereo Matching




Three cases:

- Matching patches. Cost = dissimilarity score
- Occluded from right. Cost is some constant value.
- Occluded from left. Cost is some constant value.

$$C(i,j) = \min([ C(i-1,j-1) + \text{dissimilarity}(i,j) \\ C(i-1,j) + \text{occlusionConstant}, \\ C(i,j-1) + \text{occlusionConstant}]);$$

# Cox et.al. Stereo Matching



**Recap:** want to find lowest cost path from upper left to lower right of DSI image.


At each point on the path we have three choices: step left, step down, step diagonally.

Each choice has a well-defined cost associated with it.


This problem just screams out for Dynamic Programming!  
(which, indeed, is how Cox et.al. solve the problem)

# Real Scanline Example

DSI



DP cost matrix  
(cost of optimal path from each point to END)



Every pixel in left column now is marked with either a disparity value, or an occlusion label.

Proceed for every scanline in left image.



# Example

Result of DP alg



Result without DP (independent pixels)



Result of DP alg. Black pixels = occluded.

# Occlusion Filling

Simple trick for filling in gaps caused by occlusion.




 = left occluded

Fill in left occluded pixels with value from the nearest valid pixel preceding it in the scanline.



Similarly, for right occluded, look for valid pixel to the right.


# Example



Result of DP alg with occlusion filling.

# Example

Result of DP alg with occlusion filling.




Result without DP (independent pixels)




# Example


Result of DP alg with occlusion filling.



Ground truth




# Stereo with 2D smoothness constraint



- What defines a good stereo correspondence?
  1. Match quality
    - Want each pixel to find a good match in the other image
  2. Smoothness
    - If two pixels are adjacent, they should (usually) move about the same amount



# Optimizing for match quality *and* smoothness (in any direction)



$$E = \alpha E_{\text{data}}(I_1, I_2, D) + \beta E_{\text{smooth}}(D)$$


$$E_{\text{data}} = \sum_i (W_1(i) - W_2(i + D(i)))^2$$

$$E_{\text{smooth}} = \sum_{\text{neighbors } i, j} \rho(D(i) - D(j))$$

- Energy functions of this form can be minimized using *graph cuts*

Y. Boykov, O. Veksler, and R. Zabih, [Fast Approximate Energy Minimization via Graph Cuts](#), PAMI 2001

# Results with window search



Window-based matching  
(best window size)



Ground truth

# Better results...



Graph cut method

Boykov et al., [Fast Approximate Energy Minimization via Graph Cuts](#),  
International Conference on Computer Vision, September 1999.




Ground truth

# Semi-global matching





$$E(D) = \sum_{\mathbf{p}} (C(\mathbf{p}, D_{\mathbf{p}}) + \sum_{\mathbf{q} \in N_{\mathbf{p}}} P_1 \mathbb{T}[|D_{\mathbf{p}} - D_{\mathbf{q}}| = 1] + \sum_{\mathbf{q} \in N_{\mathbf{p}}} P_2 \mathbb{T}[|D_{\mathbf{p}} - D_{\mathbf{q}}| > 1])$$

- Approximate the full smoothness optimization by considering 8 or 16 directions in two or three passes.
- Optimization looks like scanline, dynamic programming stereo, but with a 2d notion of smoothness



Stereo Processing by Semi-Global Matching and Mutual Information. Hirschmuller, PAMI 2007. **3500+** citations

# Semi-global matching



# https://vision.middlebury.edu/stereo/eval3/

Stereo

Evaluation • Datasets • Code • Submit

## Middlebury Stereo Evaluation - Version 3

Mouseover the table cells to see the produced disparity map. Clicking a cell will blink the ground truth for comparison. To change the table type, click the links below. For more information, please see the [description of new features](#).

[Submit and evaluate your own results.](#)


Set: [test dense](#) [test sparse](#) [training dense](#) [training sparse](#)

Metric: [bad 0.5](#) [bad 1.0](#) [bad 2.0](#) [bad 4.0](#) [avgerr](#) [rms](#) [A50](#) [A90](#) [A95](#) [A99](#) [time](#) [time/MP](#) [time/GD](#)

Mask: [nonocc](#) [all](#)


plot selected  show invalid [Reset sort](#) [Reference list](#)

Date	Name	Res	Weight	bad 2.0 (%)															
				Austr	AustrP	Bicyc2	Class	ClassE	Compu	Crusa	CrusaP	Djemb	DjembL	Hoops	Livgrm	Nkuba	Plants	Stairs	
				MP: 5.6 nd: 290 im0 im1 GT nonocc	MP: 5.6 nd: 290 im0 im1 GT nonocc	MP: 5.6 nd: 250 im0 im1 GT nonocc	MP: 5.7 nd: 610 im0 im1 GT nonocc	MP: 5.7 nd: 610 im0 im1 GT nonocc	MP: 1.5 nd: 256 im0 im1 GT nonocc	MP: 5.5 nd: 800 im0 im1 GT nonocc	MP: 5.5 nd: 800 im0 im1 GT nonocc	MP: 5.7 nd: 320 im0 im1 GT nonocc	MP: 5.7 nd: 320 im0 im1 GT nonocc	MP: 5.7 nd: 410 im0 im1 GT nonocc	MP: 5.9 nd: 320 im0 im1 GT nonocc	MP: 5.5 nd: 570 im0 im1 GT nonocc	MP: 5.6 nd: 320 im0 im1 GT nonocc	MP: 5.2 nd: 450 im0 im1 GT nonocc	
08/07/24	<input type="checkbox"/> AIO-Stereo	F	2.36 1	2.38 3	1.71 1	3.22 26	0.85 1	5.83 23	1.24 6	1.42 4	1.32 5	1.03 8	4.49 10	4.81 5	2.43 2	3.61 1	2.12 2	3.63 7	
08/01/24	<input type="checkbox"/> RSM	F	2.40 2	2.66 6	1.88 4	3.18 24	0.91 2	5.80 22	1.34 10	1.35 2	1.16 2	0.93 4	3.35 4	3.96 1	2.88 3	4.38 3	2.01 1	4.15 9	
11/13/23	<input type="checkbox"/> Selective-IGEV	F	2.51 3	2.54 5	1.86 3	2.51 14	1.12 6	7.22 35	1.23 5	1.36 3	1.17 3	1.16 12	4.48 9	4.83 6	2.99 4	3.79 2	2.26 5	4.72 13	
08/12/24	<input type="checkbox"/> PointerNet	F	2.69 4	2.67 7	1.84 2	3.21 25	1.51 10	7.52 40	1.29 7	1.54 6	1.17 3	1.09 10	3.59 5	3.96 1	3.10 5	5.60 5	2.29 6	4.27 10	
11/10/22	<input type="checkbox"/> DLNR	F	3.20 5	2.91 8	2.37 9	2.18 10	1.67 13	3.21 4	1.37 11	1.66 7	1.66 9	1.11 11	6.25 22	7.07 16	3.45 7	8.90 21	4.43 25	2.91 3	
06/14/24	<input type="checkbox"/> IGEV++	F	3.23 6	3.24 11	2.46 10	4.12 41	1.15 7	6.71 32	1.38 12	1.53 5	1.52 6	1.02 7	4.57 11	4.68 4	5.41 27	7.68 15	2.22 3	4.68 12	
06/27/24	<input type="checkbox"/> CAS++	F	3.33 7	4.27 37	3.72 46	3.17 23	2.17 24	2.44 1	1.33 9	2.24 17	2.01 14	1.47 24	4.04 8	8.15 19	4.97 23	5.80 7	3.73 22	3.04 4	
02/21/24	<input type="checkbox"/> ClearDepth	F	3.48 8	4.14 34	3.16 30	2.81 17	1.95 16	4.55 12	2.36 26	1.73 10	1.70 12	1.25 19	5.46 16	11.2 48	3.12 6	7.30 13	3.70 21	3.45 6	
06/06/24	<input type="checkbox"/> MoCha-V2	F	3.51 9	2.52 4	1.95 5	2.25 11	1.47 9	4.61 13	0.98 3	7.35 69	8.07 79	0.66 1	2.95 2	4.18 3	4.46 16	5.70 6	2.54 8	2.70 2	
06/05/24	<input type="checkbox"/> MGS-Stereo	F	3.57 10	3.62 17	2.93 19	3.43 29	2.66 35	6.24 29	2.54 29	2.04 14	2.15 18	1.23 18	5.81 19	8.40 22	3.56 8	6.48 10	3.18 13	4.81 14	
10/28/23	<input type="checkbox"/> SAMFormer	F	3.63 11	3.84 28	2.95 21	1.85 7	0.98 3	3.31 5	2.02 22	1.71 8	1.67 10	0.82 2	5.50 17	10.4 38	4.57 18	11.7 38	3.92 23	3.41 5	
06/13/22	<input type="checkbox"/> EAI-Stereo	F	3.68 12	4.02 30	3.32 33	2.48 13	1.42 8	4.19 10	2.37 27	2.18 16	2.01 14	1.16 12	10.2 42	8.84 25	4.00 11	7.15 12	3.14 12	6.44 25	
11/10/21	<input type="checkbox"/> CREStereo	F	3.71 13	4.73 44	3.94 49	5.07 60	1.96 17	3.02 3	1.42 13	2.28 18	2.05 17	1.51 26	6.86 23	6.35 9	4.25 14	6.01 9	4.60 28	5.49 20	
09/08/24	<input type="checkbox"/> RSD	F	3.73 14	2.13 1	1.98 6	1.71 2	2.03 20	2.63 2	0.87 2	8.66 77	9.69 96	0.96 6	2.54 1	6.82 13	2.34 1	7.76 16	2.23 4	2.57 1	
02/28/24	<input type="checkbox"/> AKD_Stereo	F	3.87 15	4.21 36	3.53 41	3.91 34	1.08 4	7.63 42	4.75 53	1.72 9	1.60 7	1.18 15	5.26 15	9.62 29	3.66 9	7.63 14	3.23 15	5.37 19	
03/04/24	<input type="checkbox"/> ET_Stereo	F	4.00 16	4.38 38	3.33 34	2.85 18	1.53 12	7.84 45	2.61 30	1.91 12	1.82 13	1.05 9	5.08 14	8.72 24	7.52 42	8.81 20	3.09 11	4.82 15	
10/09/23	<input type="checkbox"/> EGLCR-Stereo	F	4.03 17	4.69 41	2.46 10	3.70 31	2.99 47	10.7 71	2.48 28	1.95 13	1.63 8	0.94 5	5.76 18	8.17 20	3.84 10	10.3 30	2.99 10	4.87 16	
03/04/24	<input type="checkbox"/> AEACV	F	4.15 18	5.53 62	2.98 23	2.54 15	3.23 51	3.42 7	1.57 14	2.85 22	2.99 27	1.22 16	4.63 12	5.96 8	4.36 15	12.9 51	5.41 46	4.08 8	
10/30/23	<input type="checkbox"/> LoS	F	4.20 19	5.85 68	4.92 95	4.64 52	2.77 40	3.92 8	1.32 8	2.36 19	2.17 19	1.81 32	8.18 30	6.58 10	4.55 17	8.57 18	4.57 26	5.06 18	
01/31/24	<input type="checkbox"/> HART	F	4.24 20	3.13 9	2.24 8	4.16 43	1.10 5	4.01 9	2.03 23	1.86 11	1.68 11	0.85 3	9.83 37	11.0 44	8.71 51	9.65 25	3.26 16	6.96 30	
09/26/24	<input type="checkbox"/> GCAP_Stereo	F	4.31 21	5.32 54	3.40 37	2.38 12	2.16 23	11.2 78	4.44 49	2.13 15	2.04 16	1.32 21	7.16 24	8.97 26	5.03 25	8.38 17	3.22 14	6.08 24	



Medium

Right View Newkuba







# Stereo Depth Estimation Challenges

- Low-contrast ; textureless image regions
- Occlusions
- Violations of brightness constancy (e.g., specular reflections)
- Really large baselines (foreshortening and appearance change)
- Camera calibration errors

# Active stereo with structured light



- Project “structured” light patterns onto the object
  - Simplifies the correspondence problem
  - Allows us to use only one camera



L. Zhang, B. Curless, and S. M. Seitz. [Rapid Shape Acquisition Using Color Structured Light and Multi-pass Dynamic Programming](#). *3DPVT 2002*

# Kinect: Structured infrared light



---



<http://bbzipo.wordpress.com/2010/11/28/kinect-in-infrared/>

# iPhone X

---



iPhone 12 switched to lidar  
(time of flight)



# Self-driving efforts use both lidar and stereo

---





